## **ENGINE**

66 h.p., liquid cooled, 3-cylinder, overhead cam 4-cycle, electronically fuel injected

## TRANSMISSION

4-speed automatic

(automotive transaxle with electronically controlled shift)

## **DIMENSIONS**

72" Overall height with cab 140" Overall length 55" Overall width 236" Outside turning radius 128" Inside turning radius 95" Wheelbase

## **BRAKING**

Hydraulic disc brakes on all three wheels with dual circuit master cylinder Parking - Hydraulic over mechanical

## **ELECTRICAL SYSTEM**

Charging - Heavy Duty automotive alternator Lights - LED headlights DOT approved LED Stop/Tail/andTurn lights DOT approved High Visibility Stop and Turn lights Starting - 12-volt starting motor. Interlock prevents starter from operating unless shift lever is in park or neutral. Gauges - Speedometer, fuel level, hour meter Indicator lights - Oil pressure warning, three stage water temperature light (blue / below running temp, red/ above running temp, off / normal running temp) Charging system, Low fuel. Wiring - automotive grade wiring harness with abrasion resistant protective loom. Pre wired for Radio and municipal lighting options.

#### WARRANTY

One year full warranty. Please inquire for details Inquire for full offering - **OPTIONS** 

## SUSPENSION

Front - Leading link suspension Polyurethane Isolation system Rear - Independent McPherson strut

## **CLIMATE CONTROL**

Liquid core 20,000 BTU heater/defroster optional AirConditioning optional

## **STEERING**

Adjustable tilt steering wheel with center mounted horn

#### **TIRES**

165/60 14" all-season radials

#### **FEATURES**

3-wheel platform with "Tube guard" tubular steel frame
Aluminum and Plastic body panels
Optional hinged doors
Structural steel front and rear bumpers
3 point shoulder harness seat belt
Outside rear view mirrors
Electric windshield wiper with
intermittent control and windshield washer
Dome light, Floor mat
LTA (lateral thrust alarm) Safety Device
12V DC accessory port for phone, radio, etc.
50x62 in rear aluminum deck with optional
side clamping walls

## **SEAT**

One passenger adjustable forwards and backwards, with adjustable back and headrest. 3-point seat belts.

# **FUEL TANK AND FUEL MILEAGE**

9 US gallons. Up to 45 mpg. Inquire for details

# **WEIGHT CAPACITY**

Vehicle weight, 1600 lbs. GVWR, 2400 lbs. Rated capacity, 700 lbs including operator

# **COLOR**

White with all black frame and accents (standard)

## **SPEED**

Electronically governed at 40 or 45 mph.

# GO-4 GAS XTF - SPECIFICATIONS

Specifications are subject to change without notice. These vehicles comply with the U.S. D.O.T. vehicle safety standards "motorcycles", as well as meet E.P.A. and C.A.R.B. standards. Graphics illustrated on the vehicle are strictly for the purpose of this brochure. Municipalities typically outfit the vehicles with proprietary graphics.

**WESTWARD INDUSTRIES** 

TEL: 2045944100 FAX: 2042312607

EMAIL: sales@westwardindustries.com

75 Archibald Street Winnipeg. MB. Canada R2J 0V7

www.westwardindustries.com

Published 2019 - copyrights by Westward Industries Ltd.